Alfred

My Snippets

- Today; !!!td:

```
{isodate: EEEE, MMMM d, yyyy}
```

- Current Time; !!!ct:

```
{isodate: HH:mm:ss}
```

- Current Datetime; !!!cd:

```
{isodate: EEEE, MMMM d, yyyy. HH:mm:ss}
```

- Dokuwiki Today; !!!doku:

```
=== {isodate: EEEE, MMMM d, yyyy} ====
<grid>
<col sm="6">
</col>
<col sm="6">
<grid>
<col>
/*
<datatables ordering="false" auto-width="false" info="true" buttons="[
'copy', 'csv', 'print' ]" fixed-header="true">
^ Date  ^ Content  ^ Amounts  ^
</datatables>
*/
</col>
</grid>
</col>
</grid>
```

- Dokuwiki Expenses; !!!exp:

```
| {isodate:M/d}  | <label type="info">현대카드(AMEX)</label> {cursor}  |
<badge>₩</badge>  |
```

- Dokuwiki Expenses Today; !!!ext:

```
|  <label type="default">{isodate: EEEE, MMMM d, yyyy.} Total;
</label>  | | <badge>₩{cursor}</badge>  |
```

Integrate with Warp Terminal

```
on alfred_script(q)
    tell application "System Events"

        tell application "Warp" to activate

        set numWin to count (windows of process "Warp")
        if numWin < 1 then keystroke "n" using command down

        delay 0.5
        keystroke q
        keystroke return

    end tell
end alfred_script
```

References

- Integrate Warp terminal with Alfred

Alternatives for MS Windows

- ueli, This is a keystroke launcher for Windows and macOS.
- An effective launcher for windows

From:
http://theta5912.net/ - **reth**

Permanent link:
http://theta5912.net/doku.php?id=public:computer:alfred

Last update: **2024/05/01 20:47**